



Dräger X-am[®] 2800 Multi-Gas Detector

The X-am 2800 multi-gas detector measures up to four gases and is equipped with a shock-resistant CatEx SR sensor. With the Dräger Gas Detection Connect software, it offers live monitoring and powerful fleet management. Designed for personal monitoring, the X-am 2800 offers the highest level of safety at a low cost of ownership.



Benefits

Powerful data analysis in the cloud

Networking capability provides safety and efficiency: Transfer your recorded data directly and conveniently via Bluetooth to a smartphone and the Gas Detection Connect software. As an alternative, you can also transfer the data directly to the cloud with the X-dock test station, providing secure access to your data and its analysis anytime and anywhere with access to the internet.

Comfortable Fleet Management

Manage your fleet of equipment comfortably and efficiently with the X-am 2800. Save operating costs and time with fast tests, using the automatic test station X-dock, with low gas consumption or mechanical bump test station. Further advantages include powerful fleet management via our smart software solution, convenient firmware updates in the X-dock, an optional RFID transponder, and individual color marking of the devices. Sensors are durable and devices remain operational for years, with easy-to-replace spare parts, including the power supply. Dräger provides a 4-year manufacturer's warranty on the basic device, and is compatible with X-am 2500 accessories.

Tailor-Made Gas Monitoring

The X-am 2800 is small and lightweight, comfortable to wear, and easy-to-use, with large buttons for ease of use while wearing gloves. The display clearly shows important information, such as gas readings, alarms and time. The green D-light indicates that the unit is ready for use, with a simple interface. For added safety, the oxygen channel has four alarm thresholds, real pre-alarms, and main alarms for falling and rising concentrations. The X-am 2800 is approved for use in Ex zone 0, and has been tested according to protection class IP 68.

Sensors: Durable and Powerful

The newly-developed CatEx SR sensor calibrates within seconds and protects against shocks, measuring flammable vapors, such as gasoline, diesel, and nonane. The unit can also be set to measure methane, propane, hydrogen, and many other gases. The performance is complemented by Dräger's simple cross calibration concept, in which the measurement gas, calibration gas, and bump test gas can be specified individually. The X-am 2800 calculates the necessary conversions after testing, and the sensor meets the new IEC standard 60079-29-1 (International Electrotechnical Commission) standards.

With decades of experience in sensor technology, Dräger develops and produces the sensors itself, including the powerful and durable electrochemical sensors in the XXS format, resulting in lower operating costs.

Benefits

Focus on Sustainability

During the development of the X-am 2800, sustainability was priority. The durable Dräger sensors and the rechargeable power supply, which can be easily replaced with one screw, ensure a long service life. Almost all spare parts can be replaced by trained users, with remaining parts repaired by Dräger Service. In addition, the X-am 2800 is compatible with accessories from the previous series. Upon request, a reduced number of instructional manuals will be supplied, saving paper, and recycling of old devices is available.

	Dräger X-am® 2800	Dräger X-am® 5800**
Portfolio	This is the "connected" standard 1 – 4 gas monitor for Personal Air Monitoring (and Confined Space Entry in combination with the X-am pump)**	This is the "connected" 1 – 6 gas monitor for Personal Air Monitoring and Confined Space Entry (in combination with the X-am pump) and X-zone
Number of gas channels	1 – 4	1 – 6
Bluetooth	yes*	yes*
System components		
X-dock	yes	yes
Bump test Station	yes	yes
Gas Detection Connect	yes	yes
CC Vision / Gas Vision	yes	yes
X-zone 5500/5800	no	yes
X-am Pump	yes**	yes**
Sensors		
Sensor slots	1 x CatEx SR / 3 x XXS Sensors	1 x CatEx SR / XD-IR / PID / 3 x XXS (1 x Dual XXS)**
CatEx sensor (CatEx SR)	yes	yes
IR sensor (XD-IR)	no	yes
PID	no	yes
XXS Standard sensors (O ₂ , CO LC, H ₂ S LC, SO ₂ , NO ₂)	yes	yes
XXS Special sensors	no	yes
CatEx full range function	no (but thermal conductivity can be activated so that no blocking alarm occurs for gas methane)	yes (for measurement gas methane)
IR LEL sensor + XXS H ₂ HC: signal combination	no	yes
* selected countries may be excluded ** please contact Dräger on availability of this feature/instrument		

System Components



D-40484-2021

Gas Detection Connect

Dräger Gas Detection Connect is your connection to the digital future of occupational safety. The system connects individual Dräger products through a smart software solution. Thanks to location- and time-independent access, you always have access to the position and status of your gas detection equipment and workers, allowing you to protect your workforce and increase the efficiency of your plant.



D-47907-2012

Dräger X-dock® 5300/6300/6600

The Dräger X-dock® series provides you with full control of your portable Dräger gas detection instruments. Automatic bump tests and calibrations with reduced test gas consumption and short testing times save time and money. Comprehensive documentation and evaluations provide you with a clear overview.



ST-740-2006

Dräger Bump Test Station

Easy to use, stand-alone, and portable. With the Bump Test Station, you can easily carry out functionality tests of gas detection and warning devices.



D-0894-2018

Test gases and accessories

Regular calibrations and function tests are necessary for the safe operation of your equipment and are required by governing agencies. Dräger offers a full line of test gases and accessories to keep you in compliance.

System Components



Dräger CC-Vision® & Dräger Gas-Vision®

PC software for setting parameters, testing/adjusting, and reading the data.


Accessories



Charging set

Desktop charger for individual or bulk charging of instruments. Worldwide adapters are also available.

Services



Product Service

Dräger's service packages, available in our local shops or on-site at your facility, feature preventive maintenance, service, and original replacement parts to keep your equipment working and minimize downtime.



Training

The Dräger Academy has imparted well-founded and practical knowledge for over 40 years, the Dräger Academy has provided workers with the tools needed to effectively use our equipment. With over 110 authorized trainers and more than 600 available topics, we conduct over 2,400 training sessions each year, and customized training programs are available.



Rental Service

Whether it's to alleviate a temporary shortage of equipment or to procure equipment for specific applications; DrägerRental Service is an economical alternative to purchasing. Choose from our 65,000 piece inventory as well as a wide range of additional services available upon request.

Related Products

D-406-2018



Dräger X-am® 3500

The Dräger X-am® 3500, a 1- to 4-gas detector, reliably detects flammable gases and vapors as well as O₂, CO, H₂S, NO₂, and SO₂. The innovative signalling design and extensive range of accessories ensure optimum safety and easy handling.

D-6491-2017



Dräger X-am® 8000

This 1- to 7-gas detector monitors toxic and flammable gases as well as vapors and oxygen at once – in either pump or diffusion mode. Innovative signalling design and additional functions ensure safety and convenience.

Technical Data

Dimensions (W x H x D)	130 x 48 x 44 mm (5.12 x 1.89 x 1.73 in)
Weight	typically 220 to 250 g (7.76 to 8.82 oz), depending on sensor equipment
Housing	robust 2-component housing
Display	Matrix display with high resolution
Ambient conditions	
Temperature	-20 to +50 °C (-4 to 122 F) (Measurement and storage) -40 to +50 °C (-40 to 122 F) (Use in potentially explosive atmospheres)
Pressure	700 to 1300 mbar (Measurement) 800 to 1100 mbar (Use in potentially explosive atmospheres)
Relative humidity	10 to 95 % r.h. 5 to 95 % r.h. short term
Protection class	IP68
Alarms	
Visual	3 LED "red" (gas alarms) 3 LED "yellow" (device alarm)
Audible	Multi-tone > 90 dB at 30 cm (12 in)
Vibration	
Additional technical specifications	
Energy supply	NiMH battery (no dangerous goods: UN marking) required during transport), replaceable by user, rechargeable
Bluetooth®	Bluetooth 5.0 (disabled for some countries outside the EU and outside North America, but can be retrofitted. Contact DrägerService).
Operating times	Approx. 12 h (Bluetooth active) Approx. typical 100 h without Ex-sensor
Charging time	< 4 h
Ready for measurement	< 60 s after switch-on
Data logger	Application of an optimised data compression method with high accuracy and large storage capacity. (Typically data compression >90 % compared to the traditional data logger concept with adjustable interval)
Approvals	
Marking Explosion protection:	
ATEX	I M1 Ex da ia I Ma II 1G Ex da ia IIC T4 Ga (usable in Ex-Zone 0)
IECEX	Ex da ia I Ma Ex da ia IIC T4 Ga (usable in Ex-Zone 0)
CSA (USA & Canada)	CSA approval: cCSAus Class I, Zone 0, AEx da ia IIC T4 Ga Class I, Div 1, Groups A, B, C, D Class II, Div 1, Gr. E, F, G Contact Dräger for availability
EAC	
Directives	2014/34/EU (ATEX) 2014/53/EU (RED) 2011/65/EU (RoHS)
Manufacturer's warranty	
	5 years for the : XXS O ₂ , XXS CO, and XXS H ₂ S
	4 years for the device (electronics and housing)
	3 years for the CatEx SR and XXS O ₂ PR sensor (except NO ₂ (1 year) and SO ₂ (2 years))
	1 year for the energy supply (accumulator)

Ordering Information

Dräger X-am® 2800

Part numbers

Dräger X-am 2800 Ex, O₂, CO, H₂S (Settings: Factory default settings with standard alarm thresholds, unit CatEx SR: "%LEL", with power supply (rechargeable battery), without charger, CatEx SR: methane adjustment, oxygen 0 – 25 vol.-% measuring range).
(For charging, additionally e.g. the charging set Basic is required, part number: 8320333)

Order no.

VN00605

Configurator

Dräger X-am 2800 (configurator) consisting of: Basic device (with data logger), delivery with manufacturer and calibration certificate.

3703900

Configurator: up to 4 sensors can be selected, sensor configuration can be changed later in product life.

Customer-specific settings (firmware) can be selected when ordering, examples:

Measurement gas for the Ex sensor (factory setting: methane), alarm thresholds, alarm behaviour, quick menu options, D-light etc.

Power supply (battery) optional (factory setting: with battery), without charger

Instruction for use included in the standard scope of delivery in the following languages:

9300307

GER, EN, FR, ES, PT, IT, NL, RU, ZH, JA

Instruction for use available in other languages:

DA, FI, NO, SV, PL, HR, SL, SK, CS, BT, RO, HU, EL, TR, KO, ET, LV, LT

Available as download on the product page:

www.draeger.com/ifu

Part number: 9300428

Available as download on the product page:

www.draeger.com/ifu

Part number: 9300310

Technical manual available in the following languages: : GER, EN, FR, ES, RU

Selected device options when placing the order

RFID transponder

Number of instructions for use (for order n > 1)

Bluetooth® communication protocol for integration into third-party systems (GATT license)

Bluetooth® communication protocol (GATT License) for subsequent activation

Dräger X-am Open GATT License (1 pc.)

3723353

Dräger X-am Open GATT License (10 pc.)

3723354

Dräger X-am Open GATT License (50 pc.)

3723355

Slot 1: CatEx SR Sensor

Slot 2 – 4: Electrochemical Sensors in XXS Format

Ordering Information

DrägerSensors	Sample gases	Measuring range	Resolution	Expected service life	Order no.
CatEx SR (Shock Resistant) ^{1) 2)} (factory setting: methane, other measuring gases selectable)	methane, additional gases adjustable (propane, pentane, nonane, hydrogen and many more)	0 – 100 % LEL	1 % LEL	> 4 years	6851900
XXS O ₂ ¹⁾ (4 alarm thresholds)	methane oxygen	0 – 5 Vol.-% CH ₄ 0 – 25 Vol%	0.1 Vol.-% 0.1 Vol.-%	> 5 years	6810881
XXS O ₂ PR (4 alarm thresholds, increased robustness)	oxygen	0 – 30 Vol%	0.1 Vol.-%	> 5 years	6800530
XXS CO LC ¹⁾	carbon monoxide	0 – 2.000 ppm	1 ppm	> 5 years	6813210
XXS H ₂ S LC ¹⁾	hydrogen sulphide	0 – 100 ppm	0.1 ppm	> 5 years	6811525
XXS NO ₂	nitrogen dioxide	0 – 50 ppm	0.1 ppm	> 3 years	6810884
XXS SO ₂ (with KX-Filter)	sulphur dioxide	0 – 100 ppm	0.1 ppm	> 3 years	6810885
All sensors: Response time T90: < 15 s (CatEx SR: specification for gas methane/propane)					
1) Manufacturer's warranty: 3 years, The statutory rights for defects remain unaffected, Manufacturer's warranty according to the conditions listed in the technical documentation.					
2) Special calibration for the Ex sensor is possible (default setting: methane, target gas calibration and cross calibration is possible).					
CatEx SR, sample gas "Methane" Option: No blocking alarm for sample gas methane (2 sensitivity calibrations required, display: overrange)					For availability of the function: Please contact Dräger

Power supply units/chargers

Charging set Basic consisting of a desktop charger and power supply (worldwide)	8320333
Battery and charging set (2.0): NiMH supply unit T4 with desktop charger and power supply unit (complete set)	3703889
NiMH supply unit T4 (2.0) battery only	3703887
Charging adapter (for charging a rechargeable battery without X-am unit)	8326101
Desktop charger	8318639
Plug-in power supply (worldwide) for charging 1 unit	8316997
Plug-in power supply (worldwide) for up to 5 charging modules	8316994
Adapter for power plug	8325736
(only necessary for 8321849 and 8321850)	
Power supply unit 100-240 VAC; 1.33 A for up to 5 charging modules (power supply unit adapter 8325736 additionally required)	8321849
Power supply unit 100-240 VAC; 6.25 A for up to 20 charging modules (power supply unit adapter 8325736 additionally required)	8321850
Truck charger connection cable 12 V / 24 V for charging module (straight plug)	4530057
Truck charger connection cable 230 V for charging module (straight plug, for use on 230 V sockets with the vehicle installation bracket in vehicles)	8315675
Truck charger mounting bracket for a Dräger X-am® 1/2/5x00 charging module (base plate and strap). (also requires part number 4530057 or 8315675).	8318779
Replacement strap for truck charger bracket	8318788

Ordering Information

Pump accessories

Dräger X-am® Pump (external pump)	8327115
GP600 Probe (plastic), with Luer connection	8328667
Telescopic probe ES 150, stainless steel (connection for filter is included in SN 8319364 (dust/water filter)).	8316533
Floating probe (transparent), with adapter	8327654
5 m (16 ft) FKM hose, 3.2 mm, with adapters	8325705
10 m (32 ft) FKM hose, 3.2 mm, with adapters	8325706
20 m (66 ft) FKM hose, 3.2 mm, with adapters	8325707
45 m (148 ft) FKM hose, 3.2 mm, with adapters	8325712
Dust and water filter for pump inlet (replacement filter)	8319364
Dust and water filter for pump inlet (replacement filter, 20 pieces)	3705997
Confined space entry kit (free measuring) with external pump and 5 m (16 ft) FKM hose	8327117
Empty case, with space for X-am® 1/2/5x00, charging accessories, probe, gas cylinder, pump, 3 m (10 ft) hose and much more.	8327112
Other probes and hoses	On request

Calibration accessories

Calibration adapter for Dräger X-am® 1/2/5x00	8318752
Further versions and accessories Dräger X-dock®	Please contact Dräger
Automatic test station Dräger X-dock® 5300 (with master) 1/2/5x00	8321880
Dräger X-dock module X-am 125	8321890
Dräger X-dock module X-am 125+ (with charging function)	8321891
Dräger Bump Test Station for Dräger X-am® 1/2/5x00 (without gas cylinder)	8319131
Test gas: CH ₄ 2.5 vol%, O ₂ 17 vol%, CO 100 ppm, H ₂ S 25 ppm	4594655
Test gas: Other types	Please contact Dräger
Other accessories (hoses, valves, etc.)	Please contact Dräger

Accessories for measured value acquisition and configuration

Dräger CC-Vision	Freeware (www.draeger.com/ software)
Dräger GasVision license key	8325646 Trial Version (www.draeger.com/ software)
USB DIRA with USB cable, communication adapter infrared to USB (Note: Positioning is done with the calibration cradle. Pn: 8318752).	8317409

Dräger Gas Detection Connect

GDC Intro License	3719332
includes: Access, infrastructure, connection of up to 99 X-dock stations, 5,000 credits, valid for one year after activation.	
GDC Basic License	3719809
includes: IT infrastructure (data storage, maintenance, automatic feature updates, troubleshooting). 24/7 support, access	
GDC Asset License	3719810
includes: Definable number of X-dock stations, requires the Basic License	
GDC Asset Lite	3719811
includes: One X-dock station, non-expandable, does not require a Basic License	
GDC Credits	3719814
includes: Definable number of credits for sending live data, orderable in packages of 1000 credits.	

Ordering Information

Other accessories

Leather carrying case (black)	8318755
Transponder reader (for reading the optionally integrated RFID transponder)	6559283
Set of stickers X-am 2800/5800 silver (10x)	3703852
Set of stickers X-am 2800/5800 red (10x)	3703853
Set of stickers X-am 2800/5800 blue (10x)	3703854
Set of stickers X-am 2800/5800 yellow (10x)	3703855
Set of stickers X-am 2800/5800 green (10x)	3703856
Set display protection cover X-am 2800/5800 (10x)	3703857
E-set Upgrade RFID transponder (5 pcs.) (with adhesive tape)	3703898
Seal ring extractor (for changing XXS sensors).	R21402
(Selected sensors are supplied with a similar tool ex works).	

Not all products, features, or services are for sale in all countries.

Mentioned trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany

www.draeger.com

USA

Draeger, Inc.
7256 S. Sam Houston Parkway W.,
Suite 100
Houston, TX 77085
1 800 4DRAGER
(1 800 437 2437)

Find your Regional Sales
Representative at:
www.draeger.com/contact

