

GUARDIAN

FALL PROTECTION

RIDGE-IT ANCHOR

ANCHORAGE CONNECTOR

FEATURES & BENEFITS

- Highly durable stainless steel and zinc-plated steel
- Easy to install
- Discreet design
- Lightweight and durable
- Ideal for both residential construction and maintenance work
- Designed for permanent use on wpod-framed roofs



CONNECTION POINT

D-Ring

MATERIAL

Zinc-Plated Steel & Butyl strips for weatherproofing

COMPATIBLE

Fits any roof pitch

SHOWN:
PART #00500

SHOWN:
PART #00510



SPECIFICATIONS

STANDARDS:

OSHA 1910, OSHA 1926 Subpart M

WORKER CAPACITY:

130 - 420 lbs.

NOTES:

- Not repairable
- #00500 & #00510: 8 provided nails

MATERIALS:

Stainless steel
Zinc-plated steel
Butyl

PERFORMANCE:

- Maximum Users: 1

PART #	DESCRIPTION	SIZE/LENGTH	WEIGHT
00500	Ridge-It Anchor with 1 D-Ring	9 3/4"	0.8 Lbs
00510	Ridge-It Anchor with 2 D-Rings	17 1/2"	1.1 Lbs

APPLICATIONS



PERSONAL FALL ARREST:

Ridge-it Anchors may be used in Personal Fall Arrest applications to support:

- MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs.
- Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use.
- Applicable D-rings: Dorsal



RESTRAINT:

Ridge-it Anchors may be used in Restraint applications. Restraint systems:

- Prevent workers from reaching the leading edge of a fall hazard.
- Always account for fully deployed length of lanyard / SRL.
- Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs.
- No free fall is permitted.
- Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal).
- Applicable D-rings: Dorsal, Chest, Side, Shoulder.



NEED MORE INFORMATION?

P: 1.800.466.6385 | VISIT OUR WEBSITE: GUARDIANFALL.COM