

## Cross Arm Strap/ Cable Anchorage Sling

Part #	Length	Description
10786 - 10794	4' - 30'	Premium Cross Arm Strap w/ Large & Small D-rings
10420 - 10442	3', 4', 6'	Galvanized Cable w/3" O-Ring & Snap Hook Ends
10460 - 10462	3', 4', 6'	Vinyl Coated Galvanized Cable w/3" O-Ring & Snap Hook Ends
10430 - 10432	3', 4', 6'	Galvanized Cable w/Snap Hook Ends
10470 - 10472	3', 4', 6'	Vinyl Coated Galvanized Cable w/Snap Hook Ends
10410 - 10412	3', 4', 6'	Galvanized Cable w/2½" & 3" Ends
10450 - 10452	3', 4', 6'	Vinyl Coated Galvanized Cable w/2½" & 3" Ends
10400 - 10402	3', 4', 6'	Galvanized Cable w/Thimble Ends
10440 - 10442	3', 4', 6'	Vinyl Coated Galvanized Cable w/2½" & 3" Ends
01640, 01630, 01620	3', 4', 6'	Cross Arm Strap w/Loop End
01625	6'	Cross Arm Strap w/Large & Small D-Rings
10795, 10797	3', 6'	Surfacetech Web Premium Cross Arm Strap w/Large & Small D-Rings



Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations available. Not repairable. Contact customer service for details.

Cross Arm Straps/Cable Anchorage Slings are suitable for the following applications:



**Personal Fall Arrest:** Cross Arm Straps/Cable Anchorage Slings may be used in Personal Fall Arrest applications to support a MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', unless used in combination with equipment explicitly certified for free fall of up to 12'. Applicable D-ring: Dorsal.



**Restraint:** Cross Arm Straps/Cable Anchorage Slings may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

**For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.**

Materials: nylon, polyester, galvanized steel, and stainless steel

MAXIMUM 1 connection per Cross Arm Strap/Cable Anchorage Sling

Contact Guardian Fall Protection for individual product UPC-A codes.