

Rapid Deployment Rescue Ladder (RDRL)

GUARDIAN
FALL PROTECTION
PERFORMANCE SAFETY GEAR

Part #	Description
15022	Rapid Deployment Rescue Ladder. Length: 12'.
15023	Rapid Deployment Rescue Ladder Kit (RDRL). Includes: (1) 12' RDRL (15022), (2) 3' Premium Cross Arm Straps (10785), (2) Pompier Hooks, & (1) RDRL Bag (00763).
15046	Rapid Deployment Rescue Ladder Kit (RDRL). Includes: (1) 20' RDRL (15047), (2) 3' Premium Cross Arm Straps (10785), (2) Pompier Hooks, & (1) RDRL Bag (00771).
15047	Rapid Deployment Rescue Ladder. Length: 20'.



Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations available. Not repairable. Contact customer service for details.

RDRL is suitable for the following applications:



Rescue/Confined Space: RDRLs may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, Chest, Shoulder.

For all applications: combined worker weight capacity range (including all clothing, tools, and equipment) is 130-620 lbs.

Materials: aluminum, galvanized steel, zinc-plated steel, polyester, and nylon.

MAXIMUM 2 users per RDRL.

A complete and independent PFAS is REQUIRED when installing and using RDRL. All PFAS connections must be selected and deemed compatible by a Competent Person. **ALWAYS MAINTAIN 100% TIE-OFF.**

UPC-A Code(s): 15022: 672421150222; 15023: 672421150239; 15046: 672421150468; 15047: 672421150475