

Cyclone Harness Series

GUARDIAN

FALL PROTECTION

| Part # | Sizes | Description |
|-------------|-----------------|---|
| 21064-21067 | S, M-L, XL, 2XL | Cyclone Construction Harness w/Pass-Through Chest Buckle, Leg Tongue Buckles, & Waist Tongue Buckle |
| 21033-21036 | S, M-L, XL, 2XL | Cyclone Construction Harness w/Chest Quick-Connect Buckle, Leg Quick-Connect Buckles, & Waist Tongue Buckle |
| 21029-21032 | S, M-L, XL, 2XL | Cyclone Construction Harness w/Chest Quick-Connect Buckle, Leg Tongue Buckles, & Waist Tongue Buckle |
| 21052-21055 | S, M-L, XL, 2XL | Cyclone Harness w/Pass-Through Chest Buckle & Leg Tongue Buckles |
| 21045-21048 | S, M-L, XL, 2XL | Cyclone Harness w/Chest & Leg Quick-Connect Buckles |
| 21041-21044 | S, M-L, XL, 2XL | Cyclone Harness w/Chest Quick-Connect Buckle & Leg Tongue Buckles |
| 21082-21083 | M-L, XL | Cyclone Tower Harness w/Chest Quick-Connect Buckle, Leg Quick-Connect Buckles, & Waist Combination Buckle |
| 21056-21058 | S, M-L, XL | Cyclone Harness. Black/Orange w/Silver Reflective Webbing, Quick-Connect Chest, & Tongue Buckle Leg Buckles. No waist belt. |
| 21060-21062 | S, M-L, XL | Cyclone Harness. Black/Orange w/Silver Reflective Webbing, Quick-Connect Chest, Tongue Buckle Leg & Waist Belt Buckles, & Side D-rings. |

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations available. Not repairable. Contact customer service for details.



Cyclone Harnesses are suitable for the following applications:



Personal Fall Arrest: A Cyclone Harness may be used in Personal Fall Arrest applications as a component of a Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', unless used in combination with equipment explicitly certified for extended free fall. Applicable D-ring: Dorsal.



Restraint: A Cyclone Harness may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



Work Positioning: A Cyclone Harness, configured with side D-rings, may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.



Rescue/Confined Space: A Cyclone Harness may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, chest, shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.

Made from some or all of the following materials: polyester, nylon, galvanized steel, and aluminum.

Always follow all manufacturer's instructions for proper adornment and use. Some steps of adorning a harness may require assistance from another person.

Upon completely adorning a harness, Guardian Fall Protection recommends that another person, with knowledge of the safe and correct use of the harness, inspect to ensure the harness is being worn correctly.

Contact Guardian Fall Protection for individual harness model UPC codes.